

2 To 1 Serial (RS-232) AUTO SWITCH



AS-251S User Manual

Read this manual thoroughly and follow the installation procedures carefully to prevent any damage to the AS-251S and/or the devices it connects to.

©Copyright 2000 Aten® International Co., Ltd.
Manual Part No. PPAG-905-001
Printed in Taiwan 05/2002

All brand names and trademarks are the registered property of their respective owners.



Packing Checklist

- 1 x AS-251S 2 to 1 Serial (RS-232) Auto Switch
- 1 x User's Manual

If anything is damaged or missing, contact your dealer.


Overview

This easy to install Auto Switch allows two computers to share a serial printer. Since it features a light weight, compact, design, and requires no external power, it can be easily placed in any convenient location.

Features

- No External Power Required
 - Automatic and Manual Selection
 - Transparent to the User
 - Easy to Install and Operate
 - Compact size
-

Installation



1. Make sure that all the equipment to be connected up is powered Off.
 2. Use a DB-25 male to female serial cable to connect your first computer's COM1 or COM2 port to the **A** connector of the AS-251S.
 3. Use a DB-25 male to female serial cable to connect your second computer's COM1 or COM2 port to the **B** connector of the AS-251S.
 4. Use a DB-25 male to female serial cable to connect your printer's serial port to the **C** connector of the AS-251S.
 5. Turn on the power to all the equipment.
-

Switch Setting

There are two slide switches located on the unit's side panel that are used to configure the AS-251S. The one on the left determines which port has access to the printer; the one on the right sets the timeout value.



Selected Port

The port that has access to the printer is determined with this three position slide switch as follows:

Position	Result
AUTO	Under AUTO (the central position of the switch), access to the printer is automatic, and is determined on a first come first served basis. As soon as a signal is received, the switch immediately connects and stays on the port until the print job has finished.
B	Sliding the switch to the B position (the extreme right), locks the switch on the B port and locks out the A port. Only signals from the computer connected to the B port will be sent to the printer. The B LED on the unit's top panel lights (and the A LED is off) to indicate this.
A	Sliding the switch to the A position (the extreme left), locks the switch on the A port and locks out the B port. Only signals from the computer connected to the A port will be sent to the printer. The A LED on the unit's top panel lights (and the B LED is off) to indicate this.

Timeout

The timeout switch is a two position switch:

- Slide the switch to the left position for a 10 second timeout.
- Slide the switch to the right position for a 60 second timeout.

Specifications

Function	Specification
Cable Distance	15 m
Input Connectors	2 x DB-25 Female (DCE)
Output Connectors	1 x DB-25 Female (DTE)
Port Selection	Automatic / Selectable
Timeout	10 / 60 secs.
Operating Temp.	5 to 40° C

Storage Temp.	-20 to -60° C
Humidity	0 - 80% RH
Housing	Plastic
Weight	130 g
Dimensions (L x W x H)	105 x 85 x 26 mm

Limited Warranty

IN NO EVENT SHALL THE DIRECT VENDOR S LIABILITY EXCEED THE PRICE PAID FOR THE PRODUCT FORM DIRECT, INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES RESULTING FROM THE USE OF THE PRODUCT, DISK, OR ITS DOCUMENTATION.

The direct vendor makes no warranty or representation, expressed, implied, or statutory with respect to the contents or use of this documentation, and specially disclaims its quality, performance, merchantability, or fitness for any particular purpose.

The direct vendor also reserves the right to revise or update device or documentation without obligation to notify any individual or entity of such revisions, or update. For further inquiries please contact your direct vendor.